

Super Tigre® **ELECTRIC POWER**

“The easy choice in affordable electric power systems”

Balanced 11.1V 15C LiPo Packs

Putting together the right power system should be easy and affordable — and that’s what SuperTigre offers.

Simple choices make it fast and easy to find the best combo for your application. And since connectors are compatible and installed, installation and hookup are simple, too.

And like SuperTigre engines, each component is covered by a generous warranty — and designed to deliver the things modelers want most: long life; reliability; solid performance; and most of all, no-nonsense value.

Six Capacities. Simple choices. SuperTigre.

- High, 15C continuous discharge rate for consistently strong performance
- Balanced to reach the maximum of 4.2V per cell!
- Arrives with multi-strand wire leads, a standard ElectrIFly™ balancing connector and polarized, gold-plated SuperTigre 3.5 mm battery connector already attached
- 180-day limited warranty



11.1V, 640mAh LiPo Pack (SUPP1010)
Best used with: 370 Motor; 20A ESC



11.1V, 910mAh LiPo Pack (SUPP1020)
Best used with: 370 or 400 Motors; 20A ESC



11.1V, 1250mAh LiPo Pack (SUPP1030)
Best used with: 370 or 400 Motors; 20A ESC



11.1V, 1500mAh LiPo Pack (SUPP1040)
Best Used with 400 Motor & 20A ESC or .10 Motor & 30A ESC



11.1V, 1800mAh LiPo Pack (SUPP1050)
Best used with: .10 Motor & 30A ESC



11.1V, 2100mAh 15C Pack (SUPP1060)
Best used with: .10 Motor & 30A ESC

Stock #	Cont. Discharge Rate (A)	Dimensions (in / mm)	Weight (oz / g)	Applications
SUPP1010	9.6	2.6 x 1.4 x 0.7 / 65 x 35 x 18	2.3 / 66	small foamies, slow-flyers
SUPP1020	13.6	2.6 x 1.5 x 0.9 in / 65 x 38 x 24	3.3 / 94	small foamies, slow-flyers
SUPP1030	18.75	3.2 x 1.6 x 0.9 / 82 x 40 x 24	4.4 / 126	small foamies, slow-flyers
SUPP1040	22.5	3.4 x 1.6 x 1.0 / 86 x 40 x 25	5.2 / 147	large foamies, slow flyers, trainers, small scale airplanes
SUPP1050	27	4.8 x 1.7 x 0.9 / 123 x 42 x 23	6.8 / 194	large foamies, slow flyers, trainers, small scale airplanes
SUPP1060	31.5	4.8 x 1.7 x 0.9 / 123 x 42 x 24	7.5 / 214	trainers, scale airplanes

Note: Maximum recommended charge rate for all packs is 1C (1 x capacity)

Adapters & Charge Leads

- SUPM0001 3.5 mm Gold-Plated Bullet Power Connectors
- SUPM0010 ST Male LiPo to Deans® Female Ultra Plug® Adapter
- SUPM0020 ST Male LiPo to Deans Micro Plug Adapter
- SUPM0030 ST Female LiPo to Standard Female Adapter

- SUPM0040 Deans Male Ultra Plug to ST ESC Adapter
- SUPM0050 Deans Micro Battery to ST ESC Adapter
- SUPM0060 Standard Female to ST ESC Adapter
- SUPM0070 ST Male Charge Lead with Banana Plugs